

IN THE CLAIMS

1. (Currently Amended) The [[A]] smart container assembly of claim 9, further comprising:
~~a hermetically sealed storage cavity;~~
~~a monitoring assembly positioned outside of the hermetically sealed storage cavity and~~
~~including~~
a sensing mechanism;
an I/O interface;
and a recording mechanism electrically coupled to both the sensing mechanism and the
I/O interface for recording data obtained from both the sensing mechanism and the
I/O interface.
2. (Previously Presented) The assembly of claim 1 wherein the recording mechanism
comprises at least a first sub-mechanism and a second sub-mechanism wherein the first
sub-mechanism is electrically coupled to the sensing mechanism and the second sub-
mechanism is electrically coupled to an input portion of the I/O interface.
3. (Previously Presented) The assembly of claim 2 wherein the I/O interface comprises a
first sub interface electrically coupled to the first sub-mechanism of the recording
mechanism and a second sub interface coupled to the second sub-mechanism of the
recording mechanism.
4. (Currently Amended) The assembly of claim [[1]] 9, wherein the ~~container assembly~~
~~further comprises~~ a monitoring assembly receiving cavity is sized and dimensioned to
receive and retain the monitoring assembly, the receiving cavity having an environment
more similar to the environment of the storage cavity than to the environment outside of
the container assembly in regard to at least one condition the monitoring assembly is
designed to monitor.

5. (Currently Amended) The assembly of claim [[1]] 9, wherein the ~~container assembly~~ further comprises a monitoring assembly receiving cavity is sized and dimensioned to receive and retain the monitoring assembly, the receiving cavity protruding into but being hermetically isolated from the storage cavity.
6. Canceled.
7. (Currently Amended) The assembly of claim [[6]] 9 wherein the removal of the seal cap ~~and/or~~ dip tube assembly is the only way to break the hermetic seal of the storage cavity without creating a new opening into the storage cavity.
8. (Original) The assembly of claim 7 wherein the seal cap may be removed without breaking the hermetic seal between the dip tube assembly and the container, removal of the seal cap providing an outlet for any material stored in the storage cavity from the storage cavity, wherein any material flowing out of the storage cavity through the opening created by removal of the seal cap must flow through the dip tube of the dip tube assembly.
9. A smart container assembly comprising:
 - a storage container that includes a monitoring assembly receiving cavity, a dip tube orifice, an outer wall surrounding and defining a storage cavity;
 - a dip tube assembly hermetically sealed to the perimeter of the dip tube orifice;
 - a monitoring assembly positioned and removably retained within the monitoring assembly receiving cavity; and
 - a dip tube seal cap positioned within and hermetically sealed to an end of the dip tube assembly, the dip tube assembly and seal cap hermetically sealing the storage cavity.
10. (Previously Presented) A method of transporting a material comprising:
 - providing the smart container assembly of claim 1;

- placing the material to be transported within the container assembly;
- transporting the container assembly containing the material to be transported; and
- electronically querying the container assembly for information related to the contents or transportation of the container assembly.
11. (Original) The method of claim 10 further comprising electronically recording, prior to transportation of the container assembly, data relating to the material to be transported within the container assembly.
 12. (Original) The method of claim 11 wherein electronically querying the container results in the container providing at least some of the electronically recorded data relating to the material transported within the container assembly.
 13. (Original) The method of claim 10 wherein electronically querying the container results in the container providing information relating to the conditions the material was subjected to during transportation.
 14. (Original) The method of claim 10 further comprising, after transportation of the container assembly, coupling the container to a processing unit programmed to query the container for information relating to both the material transported within the container assembly and the conditions the material was subjected to during the transportation, and also programmed to use the material within the container assembly only if the contents and handling of the container assembly meet a standard programmed into or obtainable by the processing unit.
 15. (Original) The method of claim 14 wherein placing the material within the container assembly comprises at least partially hermetically sealing an opening into a storage cavity containing the material with a dip tube assembly extending into the storage cavity.
 16. (Original) The method of claim 15 wherein the material placed within the container assembly is a spin-on material.

Inventor: Alejandro R. Madrid
Serial No.: 09/825,380
Attny Dkt. No. 7210172001-3221000
Honeywell Dkt. No. H0001743 (4780)

Art Unit: 2876
Examiner: Ahshik Kim

17. The method of claim 16 wherein the material placed within the container assembly is a glass or organic polymer.

REQUEST FOR ALLOWANCE


Claims 1-5, 7-8 and 10-17 are herein rewritten to depend from allowable claim 9. The Applicant respectfully requests that the Examiner review and allow the claims as amended herein.

Dated: 6/17/2004

Respectfully submitted,

Bingham McCutchen, LLP

By:



Sandra P. Thompson, PhD, Esq.

Reg. No. 46,264

E-mail: sandra.thompson@bingham.com

Direct Line: 714-433-2622

ATTORNEYS FOR APPLICANT(S):

Plaza Tower
600 Anton Boulevard, 18th Floor
Costa Mesa, CA 92626
Tel: (714) 433-2622
Fax: (714) 433-2754

Three Embarcadero Center
San Francisco, CA 94111
Tel: (415) 393-2000
Fax: (415) 393-2286